



B4-72 series explosion-proof high pressure centrifugal ventilator

Type	Speed (r/min)	Power of motor(kw-p)	Blow rate (m ³ /h)	Full pa
2.5A	2900	0.75-2	805-1677	792-483
2.8A	2900	1.5-2	1131-2536	994-606
3.2A	2900	2.2-2	1688-3517	1300-792
	1450	1.1-4	884-1758	324-198
3.6A	2900	3.2-2	2664-5268	1578-989
	1450	1.1-4	1332-2634	393-247
4A	2900	5.5-2	4012-7419	2014-1320
	1450	1.1-4	2006-3709	501-329
4.5A	2900	7.5-2	5712-10562	2554-1673
	1450	1.1-4	2856-5281	634-416
5A	2900	15-2	7728-15445	3187-2019
	1450	2.2-4	3864-7728	790-502
6A	1450	4.0-4	6677-13353	1139-724
	960	1.5-6	4420-8841	498-317
6D	1450	4.0-4	15826-29344	1139-724
	960	1.5-6	10478-19428	498-317

8D	1450	18.5-4	7968-14773	2032-1490
	960	5.5-6	40441-56605	887-651
	730	3.0-8	26775-37476	512-376
10D	1450	Apr-55	40441-56605	3202-2532
	960	18.5-6	26775-37476	1395-1104
	730	7.5-8	20360-27497	805-637
12D	960	Jun-45	46267-64759	2013-1593
	730	18.5-8	35182-49244	1169-919