

	A	B	C	D	E	F	G	K	N	H	S	L	AC	
63	60	65	10	11	23	4	8.5	12.5	M8	175	M8	360	140	Size C and N 90-160 aircraft Zuoxiao Thread the size and depth
71	65	70	12	14	30	5	11	16	M8	185	M8	395	158	
80	67	85	12	19	40	6	15.5	21.5	M10	192	M8	400	165	
90S	76	86	22	24	50	8	20	27	M6	195	M12	415	200	
90L	76	115	22	28	60	8	20	27	M6	195	M12	440	200	
100L	83	130	22	28	60	8	24	32	M6	213	M12	525	210	
112M	90	130	22	28	60	8	24	32	M6	218	M12	545	230	
132S	100	130	22	38	80	10	33	41	M8	270	M14	660	266	
132M	100	168	22	38	80	10	33	41	M8	270	M14	700	266	
160M	120	200	24	42	110	12	37	45	M8	346	M16	750	350	YBF160 appearance for the 6 Prism uniform
160L	120	244	24	42	110	12	37	45	M8	346	M16	800	350	

Type	Output	Current	Speed	Eff.	Power	<u>Starting Torque</u>	<u>Starting Current</u>	<u>Max Torque</u>
	(W)	(A)	(r/min)	(%)	factor	Rated Torque Tst/Tn	Rated Current Lst/In	Rated Torque Tmax/Tn
YBF6312	180	0.53	2800	69	0.75	1.8	7	2
YBF6322	250	0.68	2800	72	0.78	1.8	7	2
YBF6314	120	0.47	1400	62	0.63	1.8	6.5	2
YBF6324	180	0.64	1400	64	0.67	1.8	6.5	2
YBF7112	370	0.96	2800	73.5	0.8	1.8	7	2
YBF7122	550	1.35	2800	75.5	0.82	1.8	7	2
YBF7114	250	0.82	1400	68	0.68	1.8	6.5	2
YBF7124	370	1.1	1400	70	0.73	1.8	6.5	2
YBF7116	180	0.65	910	64	0.66	1.7	6	1.9
YBF7126	250	0.88	910	65	0.67	1.7	6	1.9
YBF7128	90	0.49	680	51	0.55	1.5	5.5	1.8
YBF7138	120	0.63	680	51	0.57	1.5	5.5	1.8
YBF8012	750	1.76	2800	76.5	0.85	1.8	7	2
YBF8022	1100	2.53	2800	77	0.86	1.8	7	2
YBF8014	550	1.54	1400	73.5	0.74	1.8	6.5	2
YBF8024	750	1.99	1400	75.5	0.76	1.8	6.5	2
YBF8016	370	1.15	910	71	0.69	1.7	6	1.9

YBF8026	550	1.66	910	72	0.7	1.7	6	1.9
YBF8028	180	0.75	680	60	0.61	1.5	5.5	1.8
YBF8038	250	0.98	680	62	0.63	1.5	5.5	1.8
YBF90S-2	1500	3.38	2800	78.5	0.86	1.8	7	2
YBF90L-2	2200	4.83	2800	80.5	0.86	1.8	7	2
YBF90S-4	1100	2.97	1400	77	0.78	1.8	6.5	2
YBF90L-4	1500	3.61	1400	79	0.8	1.8	6.5	2
YBF90S-6	750	2.2	935	73	0.71	1.7	6	1.9
YBF90L-6	1100	3.1	935	74	0.73	1.7	6	1.9
YBF90S-8	370	1.33	680	68	0.63	1.5	5.5	1.8
YBF90L-8	550	1.9	680	69	0.64	1.5	5.5	1.8
YBF100L-2	3000	6.39	2820	82	0.87	1.8	7	2
YBF100L1-4	2200	5.01	1420	81	0.825	1.8	6.5	2
YBF200L2-4	3000	6.78	1420	82.5	0.815	1.8	6.5	2
YBF100L-6	1500	3.9	940	78	0.75	1.7	6	1.9
YBF112M-2	4000	8.17	2840	85.5	0.87	1.8	7	2
YBF112M-4	4000	8.77	1440	84.5	0.82	1.8	7	2
YBF112M-6	2200	5.47	940	80.5	0.76	1.7	6	1.9
YBF132S1-2	5500	11	2900	85.5	0.88	2	7	2.2
YBF132S2-2	7500	15	2900	86.5	0.88	2	7	2.2
YBF132S-4	5500	12	1440	85.5	0.84	2.2	7	2.2
YBF132M-4	7500	15	1440	87	0.85	2.2	7	2.2
YBF132S-6	3000	7.2	960	83	0.76	2	6.5	2
YBF132M1-6	4000	9.4	960	84	0.77	2	6.5	2
YBF132M2-6	5500	13	960	85.3	0.78	2	6.5	2
YBF132S-8	2200	5.8	710	81	0.71	2	5.5	2
YBF132M-8	3000	7.7	710	82	0.72	2	5.5	2
YBF160M-4	11000	23	1460	88	0.84	2.2	7	2.2
YBF160L-4	15000	30	1460	88	0.85	2.2	7	2.2
YBF160M-6	7500	17	970	86	0.78	2	6.5	2
YBF160L-6	11000	25	970	87	0.78	2	6.5	2
YBF160M1-8	4000	9.9	720	84	0.73	2	6	2
YBF160M2-8	5500	13	720	85	0.74	2	6	2

YBF160L-8	7500	18	720	86	0.75	2	5.5	2
-----------	------	----	-----	----	------	---	-----	---